

Life Is On



D Controls

Adjustable temperature and pressure controls

High-quality & great reliability thanks to Eliwell's application knowledge combined with 30-year expertise in marketing Ranco products

www.eliwell.com

Download My Eliwell APP!



It is the solution to find in real time any information on hundreds of Eliwell products for refrigeration and HVAC systems.

D Controls

Adjustable temperature and pressure controls

D16T - Temperature

		TEMPERATURE RANGES			
		-20...+15 °C -4...+59 °F	-10...+25 °C +14...+77 °F	-40...-5 °C -40...+23 °F	+5...+40 °C +41...+104 °F
SENSING ELEMENT	STRAIGHT CAPILLARY	R automatic D adjustable L 2-3-6-12 m	R automatic D adjustable L 2-3 m	R automatic D adjustable L 2 m	—
	COILED END	R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	—
	BULB	R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	—	R automatic D adjustable L 2 m
	AMBIENT (CAGE)	R automatic D adjustable	R automatic D adjustable	—	R automatic D adjustable

R = Reset D = Differential L = Sensing element length

D16P - Single pressure

		PRESSURE RANGES			
		LP -0,3...7 bar -0,4...100 psi	HP 7...31 bar 100...450 psi	HP 10...45 bar 145...650 psi	FAN 7...20 bar 100...290 psi
FITTING	7/16-20 MALE	R automatic D adjustable	R automatic D adjustable	R automatic D adjustable	R automatic D adjustable
	7/16	R manual D fixed	R manual D fixed	R manual D fixed	—
	1m with flare 7/16	R automatic D adjustable	R automatic D adjustable	—	R automatic D adjustable
	CAPILL. 1m with flare 7/16	R manual D fixed	R manual D fixed	—	—

R = Reset D = Differential

D17P - Dual pressure

		PRESSURE RANGES			
		LP -0,3...7 bar LP -0,4...100 psi	HP 7...31 bar HP 100...450 psi	LP -0,3...7 bar LP -0,4...100 psi	HP 10...45 bar HP 145...650 psi
FITTING	7/16-20 MALE	R automatic D adjustable	R automatic D fixed	R automatic D adjustable	R automatic D fixed
		R automatic D adjustable	R manual D fixed	—	R manual D fixed
		R manual D fixed	R manual D fixed	—	R manual D fixed
	CAPILL. 1m with flare 7/16	R automatic D adjustable	R automatic D fixed	—	—
		R automatic D adjustable	R manual D fixed	—	—
		R manual D fixed	R manual D fixed	—	—

R = Reset D = Differential

Available accessories



CT123407 • TDS D CONTROLS • EN • rel.12/18 • © Eliwell Controls s.r.l. 2018 - All rights reserved

ITALY - Headquarters

Eliwell Controls srl
Via dell'Industria, 15 Z.I. Paludi
32016 Alpagno (BL) - ITALY
T: +39 0437 986 111
F: +39 0437 989 066

Follow us on

Sales
T: +39 0437 986 100 (Italy)
T: +39 0437 986 200 (other countries)
E: saleseliwell@schneider-electric.com

Technical support
T: +39 0437 986 300
E: techsuppeliwell@schneider-electric.com

www.eliwell.com

Download My Eliwell APP!



It is the solution to find in real time any information on hundreds of Eliwell products for refrigeration and HVAC systems.